



## Bearing de Mexico, S.A.

25 mm x 28 mm x 20 mm SKF PCM 252820 M  
plain bearings



Bearing No. PCM 252820 M

Size	25x28x20 mm
Bore Diameter	25 mm
Outer Diameter	28 mm
Width	20 mm
d	25 mm
D	28 mm
B	20 mm
c1 min	0,1 mm
c2 min	0,2 mm
M	4 mm
Weight	0,016 Kg
Basic dynamic load rating (C)	57 kN
c <sub>1</sub> min.	0.1 mm
c <sub>1</sub> max.	0.7 mm
c <sub>2</sub> min.	0.2 mm
c <sub>2</sub> max.	1 mm
± 8	20 °
Tolerance shaft	h8
Tolerance housing	H7
Basic dynamic load rating - radial direction C	57 kN
Basic static load rating - radial direction C <sub>0</sub>	120 kN
Specific dynamic load factor K	120 N/mm <sup>2</sup>
Specific static load factor K <sub>0</sub>	250 N/mm <sup>2</sup>

PCM 252820 M Bearing 2D drawings and 3D CAD models



## Bearing de Mexico, S.A.

Factor depending on material and bearing type $K_M$	1900
Permissible sliding velocity $v$ min.	0 m/s
Permissible sliding velocity $v$ max.	2.5 m/s
Coefficient of friction $\mu$ min.	0.02
Coefficient of friction $\mu$ max.	0.2
Mass bushing	0.016 kg