




Bearing de Mexico, S.A.



71912 ACD/HCP4A Bearing 2D drawings and 3D CAD models

60 mm x 85 mm x 13 mm SKF 71912 ACD/HCP4A angular contact ball bearings

Bearing No. 71912 ACD/HCP4A

| | |
|---|-------------|
| Size | 85x60x13 mm |
| Bore Diameter | 85 mm |
| Outer Diameter | 60 mm |
| Width | 13 mm |
| d | 60 mm |
| D | 85 mm |
| B | 13 mm |
| d ₁ | 67.7 mm |
| d ₂ | 67.7 mm |
| D ₁ | 77.3 mm |
| r _{1,2} - min. | 1 mm |
| r _{3,4} - min. | 0.3 mm |
| a | 23.5 mm |
| d _a - min. | 64.6 mm |
| d _b - min. | 64.6 mm |
| D _a - max. | 80.4 mm |
| D _b - max. | 83 mm |
| r _a - max. | 1 mm |
| r _b - max. | 0.3 mm |
| d _n | 69.7 mm |
| Basic dynamic load rating - C | 18.6 kN |
| Basic static load rating - C ₀ | 14.6 kN |
| Fatigue load limit - P _u | 0.62 kN |
| Limiting speed for grease | 16000 r/min |



Bearing de Mexico, S.A.

| | |
|------------------------------------|---------------------|
| Lubrication | |
| Limiting speed for oil lubrication | 26000 mm/min |
| Ball - D_w | 7.938 mm |
| Ball - z | 24 |
| G_{ref} | 2.7 cm ³ |
| Calculation factor - e | 0.68 |
| Calculation factor - Y_2 | 0.87 |
| Calculation factor - Y_0 | 0.38 |
| Calculation factor - X_2 | 0.41 |
| Calculation factor - Y_1 | 0.92 |
| Calculation factor - Y_2 | 1.41 |
| Calculation factor - Y_0 | 0.76 |
| Calculation factor - X_2 | 0.67 |
| Preload class A - G_A | 120 N |
| Preload class B - G_B | 240 N |
| Preload class C - G_C | 480 N |
| Preload class D - G_D | 960 N |
| Calculation factor - f | 1.17 |
| Calculation factor - f_1 | 0.98 |
| Calculation factor - f_{2A} | 1 |
| Calculation factor - f_{2B} | 1.07 |
| Calculation factor - f_{2C} | 1.12 |
| Calculation factor - f_{2D} | 1.17 |
| Calculation factor - f_{HC} | 1.04 |
| Preload class A | 142 N/micron |
| Preload class B | 184 N/micron |
| Preload class C | 242 N/micron |
| Preload class D | 324 N/micron |
| | |



Bearing de Mexico, S.A.

| | |
|--|---------------------|
| d_1 | 67.7 mm |
| d_2 | 67.7 mm |
| D_1 | 77.3 mm |
| $r_{1,2}$ min. | 1 mm |
| $r_{3,4}$ min. | 0.3 mm |
| d_a min. | 64.6 mm |
| d_b min. | 64.6 mm |
| D_a max. | 80.4 mm |
| D_b max. | 83 mm |
| r_a max. | 1 mm |
| r_b max. | 0.3 mm |
| d_n | 69.7 mm |
| Basic dynamic load rating C | 18.6 kN |
| Basic static load rating C_0 | 14.6 kN |
| Fatigue load limit P_u | 0.62 kN |
| Attainable speed for grease lubrication | 16000 r/min |
| Attainable speed for oil-air lubrication | 26000 r/min |
| Ball diameter D_w | 7.938 mm |
| Number of balls z | 24 |
| Reference grease quantity G_{ref} | 2.7 cm ³ |
| Preload class A G_A | 120 N |
| Static axial stiffness, preload class A | 142 N/ μ m |
| Preload class B G_B | 240 N |
| Static axial stiffness, preload class B | 184 N/ μ m |
| Preload class C G_C | 480 N |
| Static axial stiffness, preload class C | 242 N/ μ m |
| Preload class D G_D | 960 N |
| Static axial stiffness, preload class D | 324 N/ μ m |



Bearing de Mexico, S.A.

| | |
|---|---------|
| class D | |
| Calculation factor f | 1.17 |
| Calculation factor f_1 | 0.98 |
| Calculation factor f_{2A} | 1 |
| Calculation factor f_{2B} | 1.07 |
| Calculation factor f_{2C} | 1.12 |
| Calculation factor f_{2D} | 1.17 |
| Calculation factor f_{HC} | 1.04 |
| Calculation factor e | 0.68 |
| Calculation factor (single, tandem) Y_2 | 0.87 |
| Calculation factor (single, tandem) Y_0 | 0.38 |
| Calculation factor (single, tandem) X_2 | 0.41 |
| Calculation factor (back-to-back, face-to-face) Y_1 | 0.92 |
| Calculation factor (back-to-back, face-to-face) Y_2 | 1.41 |
| Calculation factor (back-to-back, face-to-face) Y_0 | 0.76 |
| Calculation factor (back-to-back, face-to-face) X_2 | 0.67 |
| Mass bearing | 0.16 kg |